# Product Data Sheet
# SORB®XT HD40 Heavy-Duty Container TPU3014

| | |
|---|---|
| Article | SORB®XT HD40 Container TPU3014 |
| Artikel No. | 100697-TPU |
| Dimensions | 13.000x3.000x250 mm |
| Dimensions Protection Inlay | 13.000x3.000 mm |
| Dimensions Unterlay | 13.500x3.500 mm |
| Weight | 66,50 kg |
| Weight with Underlay & Drive-on Strips | 105,50 kg |
| Fabric of Container Body & Underlay | Orange Thermoplastic Polyurethane coated both sides membrane, Polyester fabric, 960 gr/m² |
| Tensile Strength of Container Body Fabric as per ASTM D 751 | 4.500 N/5 cm |
| Abrasion Resistance of Container Body Fabric as per ASTM D 3389 | 125 mg/1.000 cycles |
| Fabric of Drive-on Strips | Black Ethylene/vinyl acetate/PVC Alloy 1000 gr/m² for Visual Contrast |
| Material of Stays | Aluminium rod 50x5 mm |
| Decanting Valve | Plastic 1-1/2“ ball valve |

Department of Allegro
Capital, Logistics, Services & More GmbH

Allegro Capital, Logistics, Services & More GmbH
Klosterhofweg 64
41199 Mönchengladbach

phone: +49 2166 1268-160
e-mail: service@sorb-xt.de
www.sorb-xt.de

managing director: Wolf-Peter Korth
tax number: 102/5801/1903
VAT number.: DE308746153
CRN: 19194

bank details:
Commerzbank AG Mönchengladbach
IBAN: DE82 3104 0015 0162 1028 00
BIC: COBADEFFXXX

# Product Data Sheet
# SORB®XT HD40 Heavy-Duty Container TPU3014

## Product Information:

### Recommended use

- the HD Heavy-Duty container is designed to protect people and property in the event of an unwanted leakage of liquids such as water, petroleum and chemical substances

### Application

- place the container under the area where leakage or spillage is to be expected
- use as a collection container
- intended for short-term storage of hazardous substances and conventional technical, chemical and petroleum products

### After use

- easy to clean with soap and water after use

### Properties

- ideal for industrial plants, fuel storage and rocky banks
- mobile and foldable
- can be quickly set up on almost any work surface
- **excellent chemical resistance to kerosene**
- can be used as a decontamination zone
- impervious construction, resistant to scuffs and damage from hydrocarbons
- comes with 2 rolls of black fabric that provides a high-contrast traffic lane for vehicles and additional protection for the floor mat/protective mat
- retains its shape with aluminum rods
- collapsible ends allow vehicles to pass through

### Accessories

- carrier bag
- protective insert made of orange thermoplastic polyurethane-coated polyester fabric, 960 g/m²
- high-contrast black access strips made of the same material (PVC Alloy 1000 g/m²)
- 1-1/2" plastic ball valve
- packed in a container box 100x120x100 cm

Department of Allegro
Capital, Logistics, Services & More GmbH

Allegro Capital, Logistics, Services & More GmbH
Klosterhofweg 64
41199 Mönchengladbach

phone: +49 2166 1268-160
e-mail: service@sorb-xt.de
www.sorb-xt.de

managing director: Wolf-Peter Korth
tax number: 102/5801/1903
VAT number.: DE308746153
CRN: 19194

bank details:
Commerzbank AG Mönchengladbach
IBAN: DE82 3104 0015 0162 1028 00
BIC: COBADEFFXXX