Product Data Sheet
SORB®XT AM Absorption-Mat

Article	SORB®XT AM-Mat 500x400
Article No.	100615
Dimensions (mm)	500x400
Packing unit	Box with 50 pcs.
Weight (kg)	4,6 per PU
Absorption capacity (l)	0,8 per cutout
Colour	top side black bottom side grey

Product Information:

Recommended use

- for use on solid grounds (outside and inside)
- selective protection of soil and factory ground surfaces
- can be cut according to specific requirements
- also for preventive measures for longer periods
- absorbs all kinds of oils, fuels, coatings, lubricants and other volatile substances

Application

- place the mat below the area, where contaminated substances are likely to spill (for example train tracks, factory sites or under large machinery and trucks)

After application

- collect the contaminated blanks
- dispose of following the respective valid laws and local regulations

Storage

- store in a dry place with low humidity

Properties

- slip resistance
- PE-foil at bottom side prevents penetration in grounds
- highly absorbent; can be thermally recycled
- similar to Rail Mat but in 50x40cm blanks and absorbs water and chemicals

Department of Allegro
Allegro Capital, Logistics, Services & More GmbH
Klosterhofweg 64
41199 Mönchengladbach
phone: +49 2166 1268-160
e-mail: service@sorb-xt.de
www.sorb-xt.de
managing director: Wolf-Peter Korth
tax number: 102/5801/1903
VAT number.: DE308746153
CRN: 19194
bank details:
Commerzbank AG Mönchengladbach
IBAN: DE82 3104 0015 0162 1028 00
BIC: COBADEFFXXX